


Carpet Care

PC
460



FOR USE IN "STEAM-TYPE"
(WATER-WASHING) CARPET CLEANING MACHINES



Improve efficiency in carpet extraction cleaning, floor stripping and other cleaning procedures with this easy-to-use defoamer. Recommended for use in the reservoir of all steam type (water-washing) carpet cleaning machines and wet-vacs. This silicone based defoamer is formulated to quickly and efficiently break down foam and prevent foam buildup. This process greatly decreases the time and labor needed to complete tasks. It is always easier to prevent foam from occurring than it is to reduce foam already created. When possible, treat prior to the foam occurring.

Features	-	Related Benefits
Liquid defoamer	-	Breaks down suds that can clog lines
Made for extraction carpet machines	-	Reduces suds in reservoir caused by high suds shampoo solutions
Not greasy or oily	-	Leaves no residues in tank
Stable, water soluble solution	-	No separation after mixing
Versatile	-	Many defoaming applications
Economical	-	Highly concentrated / saves labor
Fast, efficient, effective	-	Tank empties faster (no sudsing)

Areas of Use -

Steam type carpet cleaning machines and wet-vacs

- Restaurants, hotels, motels, offices
- Hospitals, nursing homes, doctor's offices
- Schools, universities, child care centers
- Malls, retail stores
- Industrial defoaming applications where silicones may be used

To Use -

For most operations, 1 to 2 ounces added to a recovery tank eliminates foam completely. As a general rule use only 2 to 4 ounces of defoamer for every 10 gallons of receiver tank capacity. **See label for complete directions and use only as directed.**

Specification Data	
Available Sizes - 4/1G	Physical State - Liquid
Color - White Opaque	Fragrance - None added
Specific Gravity - 1.00	pH (undiluted) - Undetermined



PROFESSIONAL PRODUCTS



800.527.5722
www.carrollco.com

1TS9900460
Rev. 0205