

ENVIRO PATROL®

Cleaning for a Safer Environment

Metal Free Floor Finish

ACABADO PARA PISOS



PRODUCT DESCRIPTION

This product is designed with the newest in environmentally preferable metal-free polymer technology for sealing and finishing all types of resilient flooring. It contains NO zinc, phthalates or alkyl phenol ethoxylates to harm the environment or interfere with industrial wastewater treatment processes. This state of the art finish has exceptional gloss, durability, soil resistance, detergent resistance, recoatability, removability, and slip resistance.

This product is a combination sealer and finish that dries to a smooth, hard, clear and colorless coating in about 30 minutes under normal conditions. This finish is versatile and can be maintained using traditional maintenance procedures including scrub/recoat or high speed burnishing.

To enhance your environmentally preferable hard floor care program, use ENVIRO PATROL hard floor care products to maintain your floors while helping to protect human and environmental health.

ENVIRO PATROL Metal Free Floor Finish has been **3rd party certified by Green Seal** according to **GS-40 Environmental Standard** and is recognized by the **U.S. Environmental Protection Agency Design for the Environment (DfE) Formulator Initiative**.

AREAS OF USE

ENVIRO PATROL Metal Free Floor Finish is an environmentally preferred floor coating that can be used on most hard resilient floors as a sealer/finish. Its low odor qualities makes it a preferable product for health care, hospitals, nursing homes and school facilities.

This finish dries to a smooth, hard, and colorless coating in 30 minutes under normal conditions.

DIRECTIONS FOR USE

Thoroughly clean the floor prior to applying this product.

1. Strip floors using ENVIRO PATROL Wax and Finish Remover to remove buildups of old finishes, sealers or waxes.
2. Thoroughly rinse with cold water and let floor dry.
3. Apply thin to medium, even coats of this finish with an appropriate finish mop or applicator.
4. Allow each coat to dry before applying next coat. Drying time under normal conditions is 30 minutes.
5. Apply a maximum of 4-6 coats in a 24-hour period.

See label for other DIRECTIONS FOR USE.

FEATURES & RELATED BENEFITS

Environmentally preferable technology - Contains no zinc or other metals, APE free, phthalate free

Outstanding performance - Reduces labor costs

Sealer/Finish - Single product with dual product characteristics

Great initial gloss - No immediate burnishing needed

SPECIFICATION DATA

Available Sizes - 4/1G, 5G, 55G

Color - Milky white

Odor - Low

pH - 7.5 - 8.5

VOC's - 4.3%

Non-Volatile Solids - 20.0%

Slip Resistance - Exceeds ASTM 2047

Freeze/Thaw Stability - Three full cycles

Coverage - 3000 sq ft per gallon

Shelf Life - 1 year in original unopened containers



This product meets the Green Seal® environmental standard for industrial and institutional cleaners based on its reduced human and aquatic toxicity and reduced smog production potential.



All products displaying the EPA DfE logo have been Formulated in Partnership with EPA Design for the Environment Formulator Initiative.

