



contractor SOLUTIONS

HSF

HIGH SHINE FINISH PISO ACABADO CON ALTO BRILLO



HSF HIGH SHINE FINISH has been specifically formulated for high initial gloss and "wet look" response to burnishing. Due to its higher solids formula HSF will create this appearance with less coats than lower solids finishes.

HSF is easily maintained with less effort due to its ability to repel heel marks and soil. Its tough film does not allow dirt penetration, yet will respond to daily burnishing for that "wet-look" appearance.

Recommended for use on vinyl asbestos, vinyl, reinforced vinyl, asphalt and other types of resilient floors as well as non-resilient terrazzo floors.

Features

- Latest polymer technology
- Seals as it shines
- Designed for high traffic
- Unique polymer system
- High slip resistance
- Use with any speed buffer or burnisher
- Removes with finish dissolving strippers

Related Benefits

- Outstanding gloss and durability
- Reduce labor
- Unequaled gloss and scuff resistance
- Easy to apply, repair, and re-coat
- Reduces liability potential
- Excellent for any maintenance program
- Easy to remove

Areas of Use -

May be used with propane maintenance routines in:

- Hospitals, nursing homes, doctors offices
- Schools, universities, child care centers
- Grocery stores, malls, retail stores

To Use -

Completely strip off all old floor finish. Apply finish in thin to medium coats. It is recommended that a minimum of 4 to 5 coats of HSF be applied after floor has been stripped. **For applications, see label for complete directions and use only as directed.**

Specification Data

- | | |
|----------------------------------|-----------------------------------|
| Available Sizes - 4/1G, 5G | Physical State - Liquid |
| Color - Milky white | Fragrance - Acrylic |
| Total solids - 20% | Slip Resistance - High |
| Leveling - Excellent | Repairability - Excellent |
| Detergent Resistance - Excellent | Scuff Resistance - Excellent |
| Scratch Resistance - Excellent | Water Spot Resistance - Excellent |
| pH - 9.0 | DOT - Not regulated |
| VOCs - <1% | |

Rev. 0109 1TS9925A57

Manufactured by
CARROLL COMPANY
 Garland, TX 75041
 Havre de Grace, MD 21078
 Sante Fe Springs, CA 90670
 800.527.5722
 www.carrollco.com